

















bofa.co.uk/solder-fume-extraction.asp

ELECTRONICS Fume Extraction Solutions



1500 iQ

BOFA's V 1500 iQ high end extraction system combines extremely large filter capacity with high airflow and pressure rates, making it the ideal choice for heavy duty applications that generate large amounts of particulate and gaseous organic compounds. This unit can cater for up to 20 operators using 32mm arms as a centralised system or can be used to extract fumes from automated soldering machines.

Performance has now been further enhanced with the inclusion of several new features including BOFA's new iQ Operating System, making the new V 1500 iQ one of the most advanced system available.

The iQ system takes performance and safety parameters to a new level and ensures that maintenance, downtime and ownership costs are kept to a minimum.

OPTIONAL FEATURES:

(Volatile Organic Compound)

• Filter change / System fail signal

Larger silencing inlet/out boxes

Optional filter medias

Remote stop / start interface

VOC gas sensor


Interfacing

STANDARD FEATURES:


- iQ Operating System
- High airflow and pressure rates
- Reverse Flow Air filter technology
- DeepPleat DUO pre filter
- Automatic flow control system
- · Real time airflow reading
- High contrast display
- 'Run safe' operation
- Remote diagnostics via USB
- Independent filter condition monitoring, display and warnings
- Combined HEPA/Gas filter incorporating ACF technology
- Filters with long life and low replacement cost

High volume extraction for hand and machine

soldering applications.



For high performance and long filter life











Patented Technology - Patent No: GB2 499 812



UNITS - PART NUMBERS			OPTIONS		
Model	Voltage	Part No.	24V Stop / Start	Filter change / System failure signal	VOC Monitoring
V 1500 iQ Stainless Steel	0001/	E1372			
V 1500 iQ Powder Coated	230V	E1362	A2001	A2002	A2003

OPTION
Larger Silencing Exhaust / Inlet Boxes
A1060094


REPLACEMENT FILTERS - PART NUMBERS		
Model	DeepPleat DUO Pre Filter	Combined HEPA/Gas Filter
V 1500 iQ	A1030222	A1030297

TECHNICAL DATA		
	US	
Dimensions (HxWxD)	1197 x 600 x 790mm (47.1 x 23.6 x 31.1")	
Cabinet Construction	Brushed stainless steel / Powder coated mild steel	
Airflow / Pressure	1350m³/hr (795cfm) / 100mbar	
Electrical Data	230v 1ph 50/60Hz Full load current: 24 amps / 3.3kw	
	3Ph 7 amps per phase / 12 amps nautral	
Noise Level	< 63dBA (at typical operating speed)	
Weight	145kgs (320lbs)	
Approvals	CE	

DEEPPLEAT DUO PRE FILTER SPECIFICATIONS		
Surface Media Area	30m² approx	
Filter Media	Glass Fibre	
Filter Media Construction	Maxi Pleat Construction with Webbing Spacers	
Filter Housing	Zintec mild steel	
Filter Efficiency	F8 (95% @ 0.9 microns)	

COMBINED HEPA/GAS FILTER SPECIFICATIONS		
Surface Media Area	7.5m² approx	
HEPA Filter Media	Glass Fibre	
HEPA Media Construction	Maxi Pleat Construction with Webbing Spacers	
Filter Housing	Zintec Mild Steel	
Treated Activated Carbon	34kgs	
Filter Efficiency	99.997% @ 0.3 microns	

AIRFLOW THROUGH FILTERS Chemical Filter Fumes are held in the chemical gas filter HEPA Filter Small particulate is held in the HEPA filter Pre Filter Medium sized particulate held in the filter media Clean Air Velocity drops Contaminated Air through expansion Particulate Large particulate settles to the bottom of the DeepPleat DUO filter box





BOFA INTERNATIONAL LTD

Tel: +44 (0) 1202 699 444 Fax: +44 (0) 1202 699 446 Email: sales@bofa.co.uk Web: www.bofa.co.uk



Tel: (618) 205 5007 Fax: (866) 707 2632 Email: sales@bofaamericas.com Web: www.bofaamericas.com











