





10mm Stud

- "All personnel shall be grounded or equipotentially bonded according to the requirements below when handling ESDS. When personnel are seated at ESD protective workstations, they shall be connected to ground via a wrist strap system."

 [EN 61340-5-1 Clause 5.3.3 Personnel grounding]
- "A wrist strap system consists of three elements: the person, the wrist cord and a wrist band. To ensure that the resistance to ground of personnel is within the specifications, it is important to measure the entire system (i.e. from the person's body to the end of the ground cord)."
- "Wrist straps typically consist of a wrist band which makes contact with the wearer's skin. The wrist band is then attached to a grounding cord which is connected to the ESD ground reference."
- "The wrist band is a flexible, form-fitting device designed to make a reliable continuous connection to a person's wrist."

[CLC TR 61340-5-2 User guide Wrist Strap Clauses 4.5.2, 4.7.2.2, and 4.7.2.2.1]

- A. Fixed black glass-filled nylon cap with slotted opening to allow size adjustment.
- B. 300 Series Stainless Steel Backplate forms channel to hold up to 10 links of band allowing size adjustment.
- C. Snap studs are machined from 300 series stainless steel.
- D. 4mm snap stud fits to 4mm spring loaded medical type socket.
- E. 10mm snap stud fits to 10mm spring loaded medical type socket.
- F. Premium adjustable metal expansion wristband. Inside links are constructed of 300 Series Stainless Steel. Width of links is 16mm.
- G. 0.05mm polyphenylsulfone sheet is laminated to each link. Provides >5,000 volt RMS insulation per ASTM D149. Scratch resistant.
- H. Size is adjusted by sliding 1 to 10 links of the band into the backplate "C" channel.
- I. 300 Series Stainless Steel clip for electrical contact between snap stud and backplate.
- J. Underwriters Laboratory listing 90P1C.

Designed to satisfy wrist strap requirements of EN 61340-5-1.

Meets ESD S1.1 cuff resistance interior = 100 kilohms (1 x 10^2 ohms) Meets ESD S1.1 cuff resistance exterior = 10 megohms (1 x 10^7 ohms)

Item	Description	Circumference (fully expanded)
229615	Adjustable Metal Wristband, 4mm Stud	195mm to 245mm
<u>229610</u>	Adjustable Metal Wristband, 4mm Stud, XL	225mm to 280mm
229620	Adjustable Metal Wristband, 10mm Stud	195mm to 245mm
<u>229605</u>	Adjustable Metal Wristband, 10mm Stud, XL	225mm to 280mm
229625	Service Engineer's Wrist Strap (229620 + 230175)	195mm to 245mm

Unless otherwise noted, tolerance ±10%
Specifications and procedures subject to change without notice.



Adjustable Metal Wristband

DESCOEUROPE

DESCO EUROPE 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY, HERTFORDSHIRE, SG6 1BE, UK PHONE: +44 (0) 1462 672005

 $\hbox{E-MAIL:}\ \underline{Service@DescoEurope.com},\ \hbox{INTERNET:}\ \underline{DescoEurope.com}$

Drawing Number 229615

DATE: January 2018