

Antistatic Futter fabric – FF48

- Static dissipative knitted fabric
- For use in manufacturing ESD garments such as Sweatshirt, Cardigans, Jumping-suits
- IEC 61340-5-1 compatible
- All colors available providing Pantone number or color sample
- Composition:
 - 48% polyester
 - 48% cotton
 - 4% conductive yarn
- Weight - 280 g/sm
- Comfortable and breathable

Machine washable up to 40⁰ c
Do not bleach
Do not use acid or alkali
Ironing at Medium temperature
Tumble dry at low temperature

Durability

IEC 61340-5-1 Electrical properties maintained after more than 40 industrial launderings

Technical Information



22 Efal St. POB 3041 Kiryat-Arie, Petah-Tikva 49511, Israel • Tel: 972-3-9231311 • Fax: 972-3-9231511

Electrical properties:

	Test standard	Typical values	Requirements
Point to point resistance Rp	IEC 61340-5-1	$10^5 - 10^7 \Omega$	$R_p \leq 10^{11} \Omega$
Decay time	IEC 61340-2-1	0.5-0.9 seconds Peak voltage $U \leq 150V$	< 2 seconds To 10% of initial value (max peak voltage 1000V)



FF48 ESD Fabric	
Black	0048411
Navy Blue	0048408

We believe all the information in these pages including technical data to be reliable. However, we make no warranties expressed or implied and assume no liability regarding any use of this information

K&K preserves its right to alter the composition and materials used in manufacturing the product