

Ring-Light LED ϕ 66mm, for HD Cameras

Product No. OP-006 379



Ring-light containing 40 white LEDs for bright and homogenous illumination of objects. Designed for assembly on Optilia W10x-HD, W20x-HD and M20x-HD cameras. The compact control unit features an ON-OFF switch, brightness control and two outputs for connection to LED illumination units. With optional Segment control unit, user can toggle 4 groups of LEDs clockwise or anticlockwise.

Specification:

Ring light	
Number of LEDs	40 pcs
Colour temperature	5.000 K
Material	Aluminium
Attachment to camera	Circumferential clamp with spring and screw
Inner Diameter	ϕ 66 mm
Working distance	55–120 mm
Control unit (standard and Segment)	
Power supply	24 V DC, 250 mA, hollow pin plug 5.5 x 2.1 mm,
Connections to Ring-light /spot-light	2 x 9-pin mini DIN sockets
Other	ON-OFF switch and potentiometer wheel
Dimensions	Outer: ϕ 94 mm x 25 mm. Inner: ϕ 66 mm

Including items when you order OP-006 379:

- Ring-Light 40 LEDs ϕ 66mm
- Standard Control unit
- Power supply and mains cable
- Instructions manual

Optional accessories:

- Polarization set, OP-006 380
- Ring Light with Segment control unit, OP-006 385

